

DRP 2017 - LATE MODEL

Car# & Color _____

Date _____

Year/Make _____

Model _____

Chassis # _____

Driver _____

Phone _____

SAFETY

- | | |
|---|---|
| 1 <input type="checkbox"/> Aluminum seat with shoulder & headrest support | 21 <input type="checkbox"/> Driveshaft: Safety hoop on front half, bright color |
| 2 <input type="checkbox"/> Seat mounting and rear head support | 22 <input type="checkbox"/> No antifreeze |
| 3 <input type="checkbox"/> Heavy gauge floor pan, sealed firewalls | 23 <input type="checkbox"/> Tow hooks: Required front and rear |
| 4 <input type="checkbox"/> Safety belts: 2013 | 24 <input type="checkbox"/> Fuel cell: Top fill with check valves. No part of u-shaped fuel cell can be ahead of quick change |
| 5 <input type="checkbox"/> Shoulder harness max 2" below driver's shoulders | 25 <input type="checkbox"/> Fuel cell can: 1/8" steel or plates three sides |
| 6 <input type="checkbox"/> Kill switch: Access from both sides & labelled | 26 <input type="checkbox"/> Mounting: 1" tubing - 10" from ground |
| 7 <input type="checkbox"/> Padding: Roll bars, steering shaft | 27 <input type="checkbox"/> Rear protector bar below cell with braces |
| 8 <input type="checkbox"/> Fire exit: with dial and charged | 28 <input type="checkbox"/> Filler: Access thru deck lid, not connected to body |
| 9 <input type="checkbox"/> Roll cage: 1.75" x .090" wall | 29 <input type="checkbox"/> Battery: Mounting ahead of rear axle, 12V maximum |
| 10 <input type="checkbox"/> Door bars: 4 left, 3 right, deflector plate LS | 30 <input type="checkbox"/> Ballast: Mounting (no hose clamps), white with car # |
| 11 <input type="checkbox"/> Roof diagonal bar | 31 <input type="checkbox"/> Transponder location: 12" behind centerline rear axle |
| 12 <input type="checkbox"/> Window net: Latch up front | 32 <input type="checkbox"/> Studs long enough for threads to show |
| 13 <input type="checkbox"/> Driver's suit and gloves: Nomex | 33 <input type="checkbox"/> All drain plugs must be safety wired |
| 14 <input type="checkbox"/> Helmet: SA-2010 (SFI 31.1) | 34 <input type="checkbox"/> Oil pan not lower than cross-member |
| 15 <input type="checkbox"/> Eye protection | 35 <input type="checkbox"/> Driver with receiver - Mandatory |
| 16 <input type="checkbox"/> 95 DB max for all cars | |
| 17 <input type="checkbox"/> Foot protector bar | |
| 18 <input type="checkbox"/> Steering column: Collapsible or 2 U-joints | |
| 19 <input type="checkbox"/> Throttle return springs: 2 required | |
| 20 <input type="checkbox"/> Gas line: Steel or racing with protective routing | |

NEW FOR 2017 & REMINDERS

- 1 Rotor: 12-1/4" maximum no drilling
- 2 Vent window: 12" maximum
- 3 Wheelbase: 104" ± 1"
- 4 Brakes: No "wheel fans" or blower motor devices allowed
- 5 Rear Spoiler: 5" x 60"

ENGINE

- 1 Dart Iron Eagle numbers 10110010-10220010 allowed
- 2 One piece straight bore carb spacer (no tapered bore)
- 3 Setback: GM and Crate - 2"
LS - 3-1/2"
Others - 4"

SHOCKS

Approved non-adjustable shocks (maximum retail price of \$200) series; Afco 13T, R, S, 21, ARS 2000, Bilstein SZ, SN, Carrera 62, 65, 67, Gebesis GSO, Integra 431, Pro A, AC, TA, PG, QA1 21, 50, 62, 67. Manufacturer's components must be used, valving optional. KONI sealed adjustable (NON-Rebuildable) shocks allowed, are as follows: A Model # KON30-7436, KON30-7499, KON30-7325, KON30-9325, KON30-9436, KON30-7647. No KONI approved 9" shocks will be allowed on the front of cars. Approved KONI shocks are mandatory 7" on the front and 9" on the rear ONLY, bump stop enclosed in KONI package will NOT be allowed.

17. WEIGHT RULE – All Cars 58% left max 51% rear max 42% right min 49% front min

All weights include driver in driver's position. All weights are Pre-Race with fuel allowance of 1/2# per lap for total weight. **No moving weight, liquid or solid or weight moving devices allowed.** Ballast must be painted white and lettered with car number.

All weight are minimums/See Options chart for (+ / -) variations/Gas allowance is 1/2lb per lap

WEIGHT	ENGINE	CARB	Notes	%
2650	GM 602 Crate #19258602	Holley 650cfm 4bbl 4150 HP carburetor, part number 80541	6200 RPM Chip	58% Left Max 51% Rear Max
2750	GM Certified 604 Crate # 88958604 or 19318604	Holley 650cfm 4bbl 4150 HP carburetor, part number 80541	6700 RPM Chip	58% Left Max 51% Rear Max
2825	Limited Concept Engine	Holley-4412 500 cfm 2bbl	-	58% Left Max 51% Rear Max
2825	Any Crate w/updates 602 or 604	Holley 650cfm 4bbl 4150 HP carburetor, part number 80541	6700 RPM Chip	58% Left Max 51% Rear Max
2825	SPS LLM Spec Engine (Grandfather Clause) - See notes	Holley-4412 500 cfm 2bbl	Must have run @ SPS in 2016 season	58% Left Max 51% Rear Max
2825	LAX Engine 9 to 1 Cast Iron Intake & Exhaust	Holley-4412 500 cfm 2bbl	GM Brakes, LAX Shocks Rule	58% Left Max 51% Rear Max
2850	Wegner 5.3L sealed engine w/20lb weight plates each side	Holley-4412 500 cfm 2bbl	7600 RPM Chip	58% Left Max 51% Rear Max
2875	Mopar over 362 CID	Holley-4412 500 cfm 2bbl		58% Left Max 51% Rear Max

Weight Matrix Options Chart	Weight
Base Weight	See chart above
HEI Distributor (NO MSD)	-25
Solid Rear Axels	-25
Plain Air Cleaner no air box	-25
Aluminum Drive Shaft	+25
Steel Drive Shaft Less than 3" dia	+25
Four Piston Brake Calipers	+25
Ratcheting/Torque Sensing QC	+25
Internal clutch transmission	+50
Use chart to calculate Weight	